

RACKview™ INDUSTRIAL LCD MONITORS

RACKview™ 12.1", 15.0", 18.0"



INDUCOMP's Innovative line of RACKview™ industrial 19" rack mount LCD monitors has many features that can enhance your 19" rack system.

The RACKview™ industrial monitors can be ordered in various screen size configurations. LCD sizes include 12.1" 15.0" or 18.0".

Standard configuration includes a protective thick plexiglass for LCD screen protection. An optional touch screen can be ordered for applications that require an on screen pointing device.

RACKview monitors are hinged so that the monitor can swing open and the space behind the monitor can be accessed. In most 19" rack applications space is critical. The RACKview monitors provide access to the space so you can utilize it. Use the open space with control equipment, network hubs, UPS systems etc.

Brightness and contrast controls are behind the monitor, securing the buttons from accidental resetting.

Rackview monitors are a great addition to any 19" rack system.

Features at a Glance

- Rugged Steel construction, black durable powder coat paint
- LCD screen sizes include 12.1", 15.0", and 18.0"
- Auto resizing of screen for various resolution settings.
- Gaskets seal the screen front bezel, providing rugged front access
- Protective Plexiglass protection in front of the LCD screen
- Optional Resistive Touch screen (all models)
- Monitors are hinged on one side, providing behind monitor access
- Power switch is located on the front bezel for easy on/off access
- Brightness and contrast controls are behind the monitor, securing the buttons from accidental resetting
- Ideal for Industrial or Telecom 19" rack systems

TECHNICAL SPECIFICATIONS

RACKview™ Industrial Monitors

Enclosure:	Rugged Steel Construction, Tough black powder coat paint		
Dimensions:	Rackview™ 12.1" - 6U:	10.470" (H) x 19.0" (W) x 2.375" (D)	
	Rackview™ 15.0" - 7U:	12.220" (H) x 19.0" (W) x 2.375" (D)	
	Rackview™ 18.0" - 9U:	15.720" (H) x 19.0" (W) x 2.375" (D)	
Weight:	Rackview™ 12.1":	9.0 lbs	
	Rackview™ 15.0":	12.0 lbs	
	Rackview™ 18.0":	14.5 lbs	
Resolution / NIT: (Call for higher resolution and NIT)	Rackview™ 12.1":	800x600	280 NIT
	Rackview™ 15.0":	1024x768	250 NIT
	Rackview™ 18.0":	1280x1024	300 NIT
Non-Operating Temperature:	-20° to 60° C (all monitors)		
Operating Temperature:	0° to 50° C (all monitors)		
Operating Shock:	10g, 11ms, 1/2 sine		
Operating Vibration:	.41g, 3-500 Hz		
Video Interface:	DB15 VGA Female connector (standard), special order optional composite video (NTSC, PAL, VGA) interface		
Touch Screen Interface:	DB9 Serial Male connector (serial touch screen controller)		
Cable/Power:	Each Monitor comes standard with 6ft Male to Male VGA DB15 extender cable and External power supply with cable.		

Made in the USA **Other accessories are available upon request.**

Specifications can change at any time without notice